



- A SEA WATER DRAIN POINT, 2x
- B SEA WATER INLET, CONNECTION FOR 63 mm (2 1/2") I.D. HOSE
- C1 WET EXHAUST BEND WITH RISER, OPTION 1
- C2 EXHAUST FLANGE, OPTION 2, MAX. LOAD 9KG
- D1 FLEXIBLE SUSPENSION, STANDARD EQUIPMENT
- D2 FLEXIBLE SUSPENSION, OPTIONAL EQUIPMENT
- E1 OIL DIPSTICK AND FILLING ENGINE STARBOARD SIDE ALTERNATIVE
- E2 OIL DIPSTICK AND FILLING ENGINE PORT SIDE ALTERNATIVE
- F OUTLET FOR OIL DILGE PUMP (M8x1.5)
- G FRESH WATER FILLING (EXPANSION) TANK
- H FRESH WATER DRAIN POINT (4x)
- I OIL FILTER, 2x
- J BYPASS OIL FILTER
- K FUEL FILTER
- L PRIMER PUMP
- M FUEL DEARATION
- N CONNECTOR A
- O CONNECTOR B
- Q CONNECTION EYE (REVERSE GEARX32-POLE)
- R1 CONNECTION BATTERY POS.
- R2 CONNECTION BATTERY NEG
- S AIR FILTER
- T PRESSURE DROP INDICATOR, AIR FILTER
- U LIFTING EYE, 3x (Ø30 MIN. FRONT EYE REMOVABLE)
- V HOSE CONNECTION HOT WATER OUTLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- W HOSE CONNECTION HOT WATER INLET R1/2" I.D. HOSE, OPTIONAL EQUIPMENT
- X FUEL CONNECTION INLET
- Y FUEL CONNECTION OUTLET
- Z PRESSURE LUBRICATION OF PROP. SHAFT (1/4"-BNPSP)
- AA SEA WATER OUTLET FOR 2 1/8" I.D. HOSE (I.D. 54mm)
- AB EXTERNAL STOP CONNECTION
- AC CANZ CONNECTION
- AD EASY LINK CONNECTION
- AE ALARM WATER IN FUEL CONNECTION
- AF EMERGENCY STOP BUTTON
- AG OIL DIPSTICK AND FILLING TRANSMISSION
- AH OIL DRAIN TRANSMISSION
- AI EMERGENCY SHIFTING
- AJ OIL INLET ON OIL COOLER ISO-G 1/2"
- AK OIL OUTLET ON OIL COOLER ISO-G 1/2"
- AL CONNECTION BATTERY BACK-UP

SCALE 1:5  
 NET WEIGHT 5995KG (WITH OIL AND WATER)  
 DRY WEIGHT 5595KG (WITH OIL AND WATER)  
 DIMENSIONS IN MILLIMETRE AND INCHES

	ENGINE DIMENSIONS 0188-01 HP REVERSE GEAR ZE 325
	DISPOSITION DRAWING 21474753
	03