



SCALE: 1:5

- A SEA WATER INLET
  - B SEA WATER OUTLET (APPLIES DRY EXHAUST ELBOW)
  - C ANODE
  - D PRESSURE SENDER REVERSE GEAR (OPTION)
  - E WET EXHAUST ELBOW FOR 4" HOSE (OPTION)
  - F BYPASS FLOW FOR HOSE Ø25 MM
  - G HOSE BETWEEN OILCOOLER AND WET EXHAUST ELBOW
  - H SEA WATER DRAIN
  - I CONNECTION 33-CABLE FOR REVERSE GEAR
  - J CONNECTION SLIP VALVE FOR 33-CABLE (OPTION)
  - K PROP. SHAFT FLANGE, MAX Ø70 MM (OPTION)
  - L RUBBER MOUNTING (OPTION)
- DRY MASS APPROX. 620 KG

CONSEQUENCE CLASS III APPLIES TO PROPERTIES NOT MARKED

● CENTER OF GRAVITY

FOR OTHER DIMENSIONS,  
SEE FOLLOWING DRAWINGS:  
359078, DSA TA  
359079, DSA 1

|   |  |  |
|---|--|--|
|   |  |  |
| INSTALLATION DRAWING<br>ENGINE DSA 1/TA 2F220<br>RE-VERSION |  |  |
| 3590743   |  |  |
| 102   |  |  |